



## AA1325-02NT

### Oilite<sup>®</sup> Non-Tox

#### Sleeve

USDA H1 Approved Synthetic Lubricant:  
Non-Tox-SPD™. For Incidental Food  
Contact Applications.

Temp Range -75°F to +350°F

#### Dimensions & Tolerances

Nominal ID: 1 "  
ID Max: 1.002 "  
ID Min: 1.001 "  
Nominal OD: 1.3125 "  
OD Max: 1.315 "  
OD Min: 1.314 "  
Length: 3 " ±0.0075  
Weight: 0.396 lbs / 179.6 g

#### Press Fit

Housing Bore: 1.31208 " ±0.0005  
Shaft Diameter: 0.99692 " ±0.0002

#### Temperature

Max Temp F / C: 350 / 177  
Min Temp F / C: -75 / -59

#### Pressure Ratings

Max P: 2000 (psi)  
Max V: 1200 (sf/m)  
Max PV: 50000 (lb-ft/in<sup>2</sup>-min)  
Calculated P: 0 (psi)  
Calculated V: 0 (sf/m)  
Calculated PV: 0 (lb-ft/in<sup>2</sup>-min)

#### Material Specifications

Lubrication: [Self-Lubricating](#)  
Regulations: [USDA-H1 Certified](#)  
[Lead-Free](#)  
[Conflict Free](#)  
[RoHS Certified](#)  
[Reach Certified](#)  
Engineering Preferences: [Conducts Electricity](#)  
[Corrosion Resistant](#)  
Specifications Met: [SAE 841](#)  
[ASTM B-438 GR 1 TYPE 2](#)  
[CT-1000-K26](#)