

## **AAM1418-22FC**

# Oilite® M-Series Food-Contact

#### Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR

172.878.

Temp Range -23°C to +100°C



#### **Dimensions & Tolerances**

Nominal ID: 14 mm ID Max: 14.03 mm ID Min: 14.01 mm

Nominal OD: 18 mm OD Max: 18.05 mm OD Min: 18.03 mm

> Length: 22 mm ±0.127 Weight: 0.032 lbs / 14.5 g

## **Press Fit**

Housing Bore:  $17.98657 \text{ mm} \pm 0.013$ Shaft Diameter:  $13.91641 \text{ mm} \pm 0.005$ 

#### **Temperature**

Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23

## **Pressure Ratings**

Max P: 13.78 (N/mm<sup>2</sup>) Max V: 6.1 (m/s)

Max PV: 1.75 (N-M/mm<sup>2</sup>-s)

Calculated P: 0 (N/mm<sup>2</sup>)
Calculated V: 0 (m/s)

Calculated PV: 0 (N-M/mm<sup>2</sup>-s)

## **Material Specifications**

Lubrication: Self-Lubricating
Regulations: USDA-H1 Certified

Food Contact Certified

Lead-Free Conflict Free RoHS Certified Reach Certified

Engineering Preferences: Conducts Electricity

Corrosion Resistant

Specifications Met: SAE 841

**ASTM B-438 GR 1 TYPE 2** 

CT-1000-K26