

# AAM4050-40FC

## Oilite® M-Series Food- Contact

### Sleeve

Sintered Bronze Impregnated with Food  
Grade Mineral Oil: FDA 21 CFR  
172.878.

Temp Range -23°C to +100°C



### Dimensions & Tolerances

Nominal ID: 40 mm  
ID Max: 40.04 mm  
ID Min: 40.01 mm  
Nominal OD: 50 mm  
OD Max: 50.07 mm  
OD Min: 50.04 mm  
Length: 40 mm ±0.1905  
Weight: 0.406 lbs / 184.2 g

### Press Fit

Housing Bore: 49.9778 mm ±0.013  
Shaft Diameter: 39.87484 mm ±0.005

### Temperature

Max Temp F / C: 220 / 104  
Min Temp F / C: -10 / -23

### Pressure Ratings

Max P: 13.78 (N/mm<sup>2</sup>)  
Max V: 6.1 (m/s)  
Max PV: 1.75 (N-M/mm<sup>2</sup>-s)  
Calculated P: 0 (N/mm<sup>2</sup>)  
Calculated V: 0 (m/s)  
Calculated PV: 0 (N-M/mm<sup>2</sup>-s)

### Material Specifications

Lubrication: Self-Lubricating  
Regulations: USDA-H1 Certified  
Food Contact Certified  
Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Corrosion Resistant  
Specifications Met: SAE 841  
ASTM B-438 GR 1 TYPE 2  
CT-1000-K26