



## FF317-01

**Oilite**<sup>®</sup>

**Flange**

Sintered Bronze Impregnated with  
Synthetic Performance

Difference™ AM1-SPD™

Temp Range -35°F to +300°F

### Dimensions & Tolerances

Nominal ID: 0.25 "  
ID Max: 0.252 "  
ID Min: 0.251 "  
Nominal OD: 0.375 "  
OD Max: 0.378 "  
OD Min: 0.377 "  
Length: 0.25 " ±0.005  
Flange OD: 0.5 " ±0.005  
Flange Thickness: 0.0625 " ±0.0025  
Weight: 0.005 lbs / 2.3 g

### Press Fit

Housing Bore: 0.37574 " ±0.0005  
Shaft Diameter: 0.24789 " ±0.0002

### Temperature

Max Temp F / C: 300 / 149  
Min Temp F / C: -35 / -37

### Pressure Ratings

Max P: 2000 (psi)  
Max V: 1200 (sf/m)  
Max PV: 50000 (lb-ft/in<sup>2</sup>-min)  
Calculated P: 0 (psi)  
Calculated V: 0 (sf/m)  
Calculated PV: 0 (lb-ft/in<sup>2</sup>-min)

### Material Specifications

Lubrication: Self-Lubricating  
Regulations: Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Corrosion Resistant  
Specifications Met: **SAE 841**  
**ASTM B-438 GR 1 TYPE 2**  
**CT-1000-K26**