



## FFM1016-08NT

### Oilite<sup>®</sup> M-Series Metric Non-Tox

#### Flange

USDA H1 Approved Synthetic Lubricant:  
Non-Tox-SPD™. For Incidental Food  
Contact Applications Temp Range -59°C  
to +175°C

#### Dimensions & Tolerances

Nominal ID: 10 mm  
ID Max: 10.03 mm  
ID Min: 10.01 mm  
Nominal OD: 16 mm  
OD Max: 16.05 mm  
OD Min: 16.03 mm  
Length: 8 mm ±0.127  
Flange OD: 22 mm ±0.127  
Flange Thickness: 3 mm ±0.0635  
Weight: 0.017 lbs / 7.7 g

#### Press Fit

Housing Bore: 15.98797 mm ±0.013  
Shaft Diameter: 9.91967 mm ±0.005

#### Temperature

Max Temp F / C: 420 / 216  
Min Temp F / C: -75 / -59

#### Pressure Ratings

Max P: 13.78 (N/mm<sup>2</sup>)  
Max V: 6.1 (m/s)  
Max PV: 1.75 (N-M/mm<sup>2</sup>-s)  
Calculated P: 0 (N/mm<sup>2</sup>)  
Calculated V: 0 (m/s)  
Calculated PV: 0 (N-M/mm<sup>2</sup>-s)

#### Material Specifications

Lubrication: Self-Lubricating  
Regulations: USDA-H1 Certified  
Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Corrosion Resistant  
Specifications Met: SAE 841  
ASTM B-438 GR 1 TYPE 2  
CT-1000-K26