



## PUS-1216-08B

**Oilite<sup>®</sup> Polymer Poly-Safe  
Ultra-FDA**

### Sleeve

High-Performance Food Contact, Max  
PV 15,000

#### Dimensions & Tolerances

Nominal ID: 0.75 "  
ID Max: 0.7565 "  
ID Min: 0.7555 "  
Nominal OD: 1 "  
OD Max: 1.003 "  
OD Min: 1.002 "  
Length: 1 "  $\pm 0.005$   
Weight: lbs / 0 g

#### Press Fit

Housing Bore: 1 "  $\pm 0.0005$   
Shaft Diameter: 0.75082 "  $\pm 0.0002$

#### Temperature

Max Temp F / C: 220 / 104  
Min Temp F / C: -40 / -40

#### Pressure Ratings

Max P: 1500 (psi)  
Max V: 1000 (sf/m)  
Max PV: 15000 (lb-ft/in<sup>2</sup>-min)  
Calculated P: 0 (psi)  
Calculated V: 0 (sf/m)  
Calculated PV: 0 (lb-ft/in<sup>2</sup>-min)

#### Material Specifications

Lubrication: Self-Lubricating  
Dry Running

Regulations: USDA-H1 Certified  
Food Contact Certified  
Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified

Engineering Preferences: Washdown  
Chemical Resistant  
Corrosion Resistant  
Electrical Insulation  
STEAM

Specifications Met: