



SOAP632-11

Super Oilite[®]/PLUS

Sleeve

PTFE Additive-Reduced Friction
Synthetic Oilite Plus-SPD[™]. Extreme
Performance-Unique Applications.

Temp Range -60°F to +300°F

Dimensions & Tolerances

Nominal ID: 0.5 "
ID Max: 0.502 "
ID Min: 0.501 "
Nominal OD: 0.625 "
OD Max: 0.628 "
OD Min: 0.627 "
Length: 1.25 " ±0.01
Weight: 0.034 lbs / 15.4 g

Press Fit

Housing Bore: 0.6253 " ±0.0005
Shaft Diameter: 0.49707 " ±0.0002

Temperature

Max Temp F / C: 300 / 149
Min Temp F / C: -60 / -51

Pressure Ratings

Max P: 4000 (psi)
Max V: 225 (sf/m)
Max PV: 35000 (lb-ft/in²-min)
Calculated P: 0 (psi)
Calculated V: 0 (sf/m)
Calculated PV: 0 (lb-ft/in²-min)

Material Specifications

Lubrication: Self-Lubricating
Regulations: Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Conducts Electricity
Specifications Met: SAE 863
ASTM B-439 GR 4
FC-2000-K30