



SOFM5060-35

Super Oilite[®] M-Series

Metric

Flange

Iron-Based Sintered Product
Impregnated with Extreme Pressure
Synthetic AM3-SPD™. Higher Load,
Slower Speed Designs Economic
Alternative Material.

Temp Range -26°C to +149°C

Dimensions & Tolerances

Nominal ID: 50 mm
ID Max: 50.06 mm
ID Min: 50.01 mm
Nominal OD: 60 mm
OD Max: 60.1 mm
OD Min: 60.05 mm
Length: 35 mm ±0.4
Flange OD: 70 mm ±0.4
Flange Thickness: 5 mm ±0.2
Weight: 0.678 lbs / 307.5 g

Press Fit

Housing Bore: 59.98969 mm ±0.013
Shaft Diameter: 49.86592 mm ±0.005

Temperature

Max Temp F / C: 300 / 149
Min Temp F / C: -15 / -26

Pressure Ratings

Max P: 27.56 (N/mm²)
Max V: 1.14 (m/s)
Max PV: 1.225 (N-M/mm²-s)
Calculated P: 0 (N/mm²)
Calculated V: 0 (m/s)
Calculated PV: 0 (N-M/mm²-s)

Material Specifications

Lubrication: Self-Lubricating
Regulations: Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Conducts Electricity
Specifications Met: SAE 863
ASTM B-439 GR 4
FC-2000-K30