



SOFMP0306-06

Super Oilite[®] M-Series Metric/PLUS

Flange

PTFE Additive-Reduced Friction
Synthetic Oilite[®] Plus-SPD[™]. Extreme
Performance-Unique Applications.

Temp Range -50°C to +149°C

Dimensions & Tolerances

Nominal ID: 3 mm
ID Max: 3.025 mm
ID Min: 3 mm
Nominal OD: 6 mm
OD Max: 6.045 mm
OD Min: 6.02 mm
Length: 6 mm ± 0.25
Flange OD: 9 mm ± 0.25
Flange Thickness: 1.5 mm ± 0.125
Weight: 0.002 lbs / 0.9 g

Press Fit

Housing Bore: 5.98428 mm ± 0.013
Shaft Diameter: 2.91174 mm ± 0.005

Temperature

Max Temp F / C: 300 / 149
Min Temp F / C: -60 / -51

Pressure Ratings

Max P: 27.56 (N/mm²)
Max V: 1.14 (m/s)
Max PV: 1.225 (N-M/mm²-s)
Calculated P: 0 (N/mm²)
Calculated V: 0 (m/s)
Calculated PV: 0 (N-M/mm²-s)

Material Specifications

Lubrication: Self-Lubricating
Regulations: Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Conducts Electricity
Specifications Met: SAE 863
ASTM B-439 GR 4
FC-2000-K30