



TP2304-02

Oilite[®]/PLUS

Thrust

PTFE Additive-Reduced Friction
Synthetic Oilite[®]/Plus-SPD[™].

Extreme Performance-Unique
Applications.

Temp Range -60°F to +300°F

Dimensions & Tolerances

Nominal ID: 1.25 "
ID Max: 1.27 "
ID Min: 1.26 "
Nominal OD: 2.375 "
OD Max: 2.39 "
OD Min: 2.36 "
Length: 0.125 " ±0.0025
Weight: 0.09 lbs / 40.8 g

Press Fit

Housing Bore: 2.38608 " ±0.0005
Shaft Diameter: 1.26339 " ±0.0002

Temperature

Max Temp F / C: 300 / 149
Min Temp F / C: -60 / -51

Pressure Ratings

Max P: 2000 (psi)
Max V: 1200 (sf/m)
Max PV: 50000 (lb-ft/in²-min)
Calculated P: 0 (psi)
Calculated V: 0 (sf/m)
Calculated PV: 0 (lb-ft/in²-min)

Material Specifications

Lubrication: Self-Lubricating
Regulations: Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Conducts Electricity
Corrosion Resistant
Specifications Met: SAE 841
ASTM B-438 GR 1 TYPE 2
CT-1000-K26