



TT1800-01

Oilite[®]

Thrust

Sintered Bronze Impregnated with
Synthetic Performance

Difference™ AM1-SPD™

Temp Range -35°F to +300°F

Dimensions & Tolerances

Nominal ID: 1.125 "
ID Max: 1.145 "
ID Min: 1.135 "
Nominal OD: 1.875 "
OD Max: 1.89 "
OD Min: 1.86 "
Length: 0.125 " ±0.0025
Weight: 0.051 lbs / 23.1 g

Press Fit

Housing Bore: 1.88643 " ±0.0005
Shaft Diameter: 1.13876 " ±0.0002

Temperature

Max Temp F / C: 300 / 149
Min Temp F / C: -35 / -37

Pressure Ratings

Max P: 2000 (psi)
Max V: 1200 (sf/m)
Max PV: 50000 (lb-ft/in²-min)
Calculated P: 0 (psi)
Calculated V: 0 (sf/m)
Calculated PV: 0 (lb-ft/in²-min)

Material Specifications

Lubrication: Self-Lubricating
Regulations: Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Conducts Electricity
Corrosion Resistant
Specifications Met: SAE 841
ASTM B-438 GR 1 TYPE 2
CT-1000-K26