



VF-2024-12B

Oilite[®] Polymer PTFE

Flange

Good Chemical Resistance -Ultra Low
Friction, Max PV 1,000

Dimensions & Tolerances

Nominal ID: 1.25 "
ID Max: 1.254 "
ID Min: 1.25 "
Nominal OD: 1.5 "
OD Max: 1.504 "
OD Min: 1.5 "
Length: 1.5 " ± 0.005
Flange OD: 1.75 " ± 0.007
Flange Thickness: 0.125 " ± 0.005
Weight: lbs / 0 g

Press Fit

Housing Bore: 1.4986 " ± 0.0005
Shaft Diameter: 1.24168 " ± 0.0002

Temperature

Max Temp F / C: 500 / 260
Min Temp F / C: -325 / -198

Pressure Ratings

Max P: 500 (psi)
Max V: 100 (sf/m)
Max PV: 1000 (lb-ft/in²-min)
Calculated P: 0 (psi)
Calculated V: 0 (sf/m)
Calculated PV: 0 (lb-ft/in²-min)

Material Specifications

Lubrication: Self-Lubricating
Dry Running
Regulations: USDA-H1 Certified
Food Contact Certified
Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Washdown
Chemical Resistant
Corrosion Resistant
Electrical Insulation
STEAM
Specifications Met: