



VS-1824-30MB

Oilite[®] Polymer PTFE Metric

Sleeve

Good Chemical Resistance -Ultra Low Friction.

Dimensions & Tolerances

Nominal ID: 18 mm
ID Max: 18.05 mm
ID Min: 18 mm
Nominal OD: 24 mm
OD Max: 24.05 mm
OD Min: 24 mm
Length: 30 mm ± 0.127
Weight: lbs / 0 g

Press Fit

Housing Bore: 23.92408 mm ± 0.013
Shaft Diameter: 17.75517 mm ± 0.005

Temperature

Max Temp F / C: 500 / 260
Min Temp F / C: -325 / -198

Pressure Ratings

Max P: 3.45 (N/mm²)
Max V: 0.51 (m/s)
Max PV: 0.04 (N-M/mm²-s)
Calculated P: 0 (N/mm²)
Calculated V: 0 (m/s)
Calculated PV: 0 (N-M/mm²-s)

Material Specifications

Lubrication: Self-Lubricating
Dry Running

Regulations: USDA-H1 Certified
Food Contact Certified
Lead-Free
Conflict Free
RoHS Certified
Reach Certified

Engineering Preferences: Washdown
Chemical Resistant
Corrosion Resistant
Electrical Insulation
STEAM

Specifications Met: