



VSPF-0305-02B

**Oilite[®] Polymer Vespel[®]
SP-21**

Flange

Ultra-High Performance Bearing Grade,
Max PV 300,000, Vespel[®] is a
Trademark of DuPont

Dimensions & Tolerances

Nominal ID: 0.1875 "
ID Max: 0.191 "
ID Min: 0.19 "
Nominal OD: 0.3125 "
OD Max: 0.314 "
OD Min: 0.313 "
Length: 0.25 " ±0.005
Flange OD: 0.4375 " ±0.005
Flange Thickness: 0.0625 " ±0.0025
Weight: lbs / 0 g

Press Fit

Housing Bore: 0.31155 " ±0.0005
Shaft Diameter: 0.18616 " ±0.0002

Temperature

Max Temp F / C: 550 / 288
Min Temp F / C: -400 / -240

Pressure Ratings

Max P: 4900 (psi)
Max V: 3000 (sf/m)
Max PV: 300000 (lb-ft/in²-min)
Calculated P: 0 (psi)
Calculated V: 0 (sf/m)
Calculated PV: 0 (lb-ft/in²-min)

Material Specifications

Lubrication: Self-Lubricating
Dry Running
Regulations: Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Chemical Resistant
Corrosion Resistant
Electrical Insulation
Specifications Met: