



WS-0810-04B

Oilite[®] Polymer Acetal

Sleeve

Bearing Grade, Good Chemical
Resistance, Low Moisture Absorption,
Max PV 2,700

Dimensions & Tolerances

Nominal ID: 0.5 "
ID Max: 0.502 "
ID Min: 0.5 "
Nominal OD: 0.625 "
OD Max: 0.627 "
OD Min: 0.625 "
Length: 0.5 " ± 0.005
Weight: lbs / 0 g

Press Fit

Housing Bore: 0.6243 " ± 0.0005
Shaft Diameter: 0.49675 " ± 0.0002

Temperature

Max Temp F / C: 180 / 82
Min Temp F / C: -40 / -40

Pressure Ratings

Max P: 1000 (psi)
Max V: 1000 (sf/m)
Max PV: 2700 (lb-ft/in²-min)
Calculated P: 0 (psi)
Calculated V: 0 (sf/m)
Calculated PV: 0 (lb-ft/in²-min)

Material Specifications

Lubrication: Self-Lubricating
Dry Running
Regulations: Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Washdown
Chemical Resistant
Corrosion Resistant
Electrical Insulation

Specifications Met: