## **Oilite**<sup>®</sup> SYNTHETIC PERFORMANCE DIFFERENCE®

## AA1011-04FC

## **Oilite® Food-Contact**

## Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR 172.878.

Temp Range -10°F to +220°F



Dimensions	&	Tolerances
	-	1010101000

ID Max: 0.628 ID Min: 0.627 Nominal OD: 1 " OD Max: 1.003 OD Min: 1.002 Length: 1.125 Weight: 0.126 <b>Press Fit</b> Housing Bore: 1.000 Shaft Diameter: 0.623	5 " 5 " <sup>+</sup> ±0.005 lbs / 57.2 g 8 " ±0.0005 31 " ±0.0002
Nominal OD: 1 " OD Max: 1.003 OD Min: 1.002 Length: 1.125 Weight: 0.126 Press Fit Housing Bore: 1.000	5 " 5 " " ±0.005 Ibs / 57.2 g 8 " ±0.0005 31 " ±0.0002
OD Max: 1.003 OD Min: 1.002 Length: 1.125 Weight: 0.126 Press Fit Housing Bore: 1.000	5 " " ±0.005 Ibs / 57.2 g 8 " ±0.0005 31 " ±0.0002
OD Min: 1.002 Length: 1.125 Weight: 0.126 Press Fit Housing Bore: 1.000	5 " " ±0.005 Ibs / 57.2 g 8 " ±0.0005 31 " ±0.0002
Length: 1.125 Weight: 0.126 Press Fit Housing Bore: 1.000	" ±0.005 lbs / 57.2 g 8 " ±0.0005 31 " ±0.0002
Weight: 0.126 Press Fit Housing Bore: 1.000	lbs / 57.2 g 8 " ±0.0005 31 " ±0.0002
Press Fit Housing Bore: 1.000	8 " ±0.0005 31 " ±0.0002
Housing Bore: 1.000	31 " ±0.0002
-	31 " ±0.0002
Shaft Diameter: 0.623	
	104
Temperature	104
Max Temp F / C: 220 /	тот
Min Temp F / C: -10 / -	-23
Pressure Ratings	
Max P: 2000	(psi)
Max V: 1200	(sf/m)
Max PV: 5000	) (lb-ft/in <sup>2</sup> -min)
Calculated P: 0 (psi	)
Calculated V: 0 (sf/r	n)
Calculated PV: 0 (lb-t	it/in <sup>2</sup> -min)
Material Specifications	
Lubrication: Self-L	ubricating
Lead- Confl RoHS	Contact Certified
Engineering Preferences: Cond Corro	ucts Electricity sion Resistant
	841 / B-438 GR 1 TYPE 2 000-K26

Preferred Supplier -Beemer Precision, Inc. All Products Made in the U.S.A Contact (215) 646-8440 https://oilite.com Beemer Precision, Inc. ("Beemer") supplies these drawings and specifications for illustration purposes only and without representation or warranty of any kind whatsoever. The buyer is solely responsible for determining whether a bearing is suitable for the buyer's application. Dimensions, tolerances, and materials may change at any time. All bearing sales are subject to Beemer's Standard Terms and Conditions of Sale, which may be found <u>here</u> Copyright Beemer Precision, Inc.