

# AA1109-06FC

# Oilite® Food-Contact

## Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR

172.878.

Temp Range -10°F to +220°F



#### **Dimensions & Tolerances**

Nominal ID: 0.875 "

ID Max: 0.877 "

ID Min: 0.876 "

Nominal OD: 1.125 "
OD Max: 1.129 "
OD Min: 1.128 "

Length: 1.375 " ±0.005 Weight: 0.13 lbs / 59 g

#### **Press Fit**

Housing Bore: 1.12621 " ±0.0005 Shaft Diameter: 0.8721 " ±0.0002

#### **Temperature**

Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23

## **Pressure Ratings**

Max P: 2000 (psi) Max V: 1200 (sf/m)

Max PV: 50000 (lb-ft/in<sup>2</sup>-min)

Calculated P: 0 (psi)
Calculated V: 0 (sf/m)
Calculated PV: 0 (lb-ft/in<sup>2</sup>-min)

# **Material Specifications**

Lubrication: Self-Lubricating
Regulations: USDA-H1 Certified

Food Contact Certified

Lead-Free Conflict Free RoHS Certified Reach Certified

Engineering Preferences: Conducts Electricity

Corrosion Resistant

Specifications Met: SAE 841

**ASTM B-438 GR 1 TYPE 2** 

CT-1000-K26