Oilite[®] SYNTHETIC PERFORMANCE DIFFERENCE®

AA1110-03FC

Oilite® Food-Contact

Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR 172.878.

Temp Range -10°F to +220°F



Naminal ID: 1 "

Dimensions & Tolerances

Specifications Met:	SAE 841 ASTM B-438 GR 1 TYPE 2 CT-1000-K26
Engineering Preferences:	Corrosion Resistant
rtogulationo.	Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified
	Self-Lubricating USDA-H1 Certified
Material Specifications	
Calculated PV:	0 (lb-ft/in ² -min)
Calculated V:	
Calculated P:	
	50000 (lb-ft/in ² -min)
	1200 (sf/m)
-	2000 (psi)
Min Temp F / C: Pressure Ratings	-10/-23
Max Temp F / C:	
Temperature	000 / 40 4
	0.99604 " ±0.0002
-	1.12521 " ±0.0005
Press Fit	
Weight:	0.062 lbs / 28.1 g
Length:	1.25 " ±0.005
OD Min:	1.127 "
OD Max:	
Nominal OD:	
ID Min:	
Nominal ID: ID Max:	

Beemer Precision, Inc. ("Beemer") supplies these drawings and specifications for illustration purposes only and without representation or warranty of any kind whatsoever. The buyer is solely responsible for determining whether a bearing is suitable for the buyer's application. Dimensions, tolerances, and materials may change at any time. All bearing sales are subject to Beemer's Standard Terms and Conditions of Sale, which may be found <u>here</u> Copyright Beemer Precision, Inc.