

AA1233-05FC

Oilite® Food-Contact

Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR

172.878.

Temp Range -10°F to +220°F



Dimensions & Tolerances

Nominal ID: 1 "

ID Max: 1.003 "

ID Min: 1.002 "

Nominal OD: 1.25 "

OD Max: 1.254 "

OD Min: 1.253 "

Length: 1.25 " ±0.005

Weight: 0.129 lbs / 58.5 g

Press Fit

Housing Bore: 1.25112 " ±0.0005

Shaft Diameter: 0.99796 " ±0.0002

Temperature

Max Temp F / C: 220 / 104

Min Temp F / C: -10 / -23

Pressure Ratings

Max P: 2000 (psi)

Max V: 1200 (sf/m)

Max PV: 50000 (lb-ft/in²-min)

Calculated P: 0 (psi)

Calculated V: 0 (sf/m)

Calculated PV: 0 (lb-ft/in²-min)

Material Specifications

Lubrication: Self-Lubricating

Regulations: USDA-H1 Certified

Food Contact Certified

Lead-Free

Conflict Free

RoHS Certified

Reach Certified

Engineering Preferences: Conducts Electricity

Corrosion Resistant

Specifications Met: SAE 841

ASTM B-438 GR 1 TYPE 2

CT-1000-K26