

AA1318-04FC

Oilite® Food-Contact

Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR

172.878.

Temp Range -10°F to +220°F



Dimensions & Tolerances

Nominal ID: 1.125 "

ID Max: 1.128 "

ID Min: 1.127 "

Nominal OD: 1.3125 "

OD Max: 1.3165 " OD Min: 1.3155 "

> Length: 1.75 " ±0.0075 Weight: 0.203 lbs / 92.1 g

Press Fit

Housing Bore: 1.31358 " ±0.0005 Shaft Diameter: 1.12286 " ±0.0002

Temperature

Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23

Pressure Ratings

Max P: 2000 (psi)
Max V: 1200 (sf/m)

Max PV: 50000 (lb-ft/in²-min)

Calculated P: 0 (psi)
Calculated V: 0 (sf/m)

Calculated PV: 0 (lb-ft/in²-min)

Material Specifications

Lubrication: Self-Lubricating
Regulations: USDA-H1 Certified

Food Contact Certified

Lead-Free Conflict Free RoHS Certified Reach Certified

Engineering Preferences: Conducts Electricity

Corrosion Resistant

Specifications Met: SAE 841

ASTM B-438 GR 1 TYPE 2

CT-1000-K26