Oilite[®] SYNTHETIC PERFORMANCE DIFFERENCE®

AA1319-13FC

Oilite® Food-Contact

Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR 172.878.

Temp Range -10°F to +220°F



Dimensions & Tolerances

Housing Bore: 1.37603 " ±0.0005 Shaft Diameter: 1.12382 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated PV: 0 (lb-ft/in ² -min)	Nominal ID:	1.125 "
Nominal OD: 1.375 " OD Max: 1.379 " OD Min: 1.378 " Length: 1.5 " ±0.005 Weight: 0.171 lbs / 77.6 g Press Fit Housing Bore: 1.37603 " ±0.0005 Shaft Diameter: 1.12382 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated PV: 0 (lb-ft/in ² -min) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified R	ID Max:	1.129 "
OD Max: 1.379 " OD Min: 1.378 " Length: 1.5 " ±0.005 Weight: 0.171 lbs / 77.6 g Press Fit Housing Bore: 1.37603 " ±0.0005 Shaft Diameter: 1.12382 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: 220 / 104 Min Temp F / C: 10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max V: 1200 (sf/m) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated P: 0 (sf/m) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free Conflict Free Confl	ID Min:	1.128 "
OD Min: 1.378 " Length: 1.5 " ±0.005 Weight: 0.171 lbs / 77.6 g Press Fit Housing Bore: 1.37603 " ±0.0005 Shaft Diameter: 1.12382 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max V: 1200 (sf/m) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated P: 0 (sf/m) Calculated V: 0 (sf/m) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free Conflict Fre	Nominal OD:	1.375 "
Length: 1.5 " ±0.005 Weight: 0.171 lbs / 77.6 g Press Fit Housing Bore: 1.37603 " ±0.0005 Shaft Diameter: 1.12382 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated V: 0 (sf/m) Calculated V: 0 (b-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified	OD Max:	1.379 "
Weight: 0.171 lbs / 77.6 g Press Fit Housing Bore: 1.37603 " ±0.0005 Shaft Diameter: 1.12382 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max V: 1200 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Free Conflict Free RoHS Certified Reach Certified Reach Certified Reach Certified Reach Certified Reach Certified Reach Certified Resultions: Conducts Electricity	OD Min:	1.378 "
Press Fit Housing Bore: 1.37603 " ±0.0005 Shaft Diameter: 1.12382 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated P: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Reach Certified Reguneering Preferences: Conducts Electricity Corrosion Resistant	Length:	1.5 " ±0.005
Housing Bore: 1.37603 " ±0.0005 Shaft Diameter: 1.12382 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max V: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Reach Certified Reach Certified Reach Certified Reach Certified	Weight:	0.171 lbs / 77.6 g
Shaft Diameter: 1.12382 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max V: 1200 (sf/m) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Reach Certified Engineering Preferences: Conducts Electricity Corrosion Resistant	Press Fit	
Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Cert	Housing Bore:	1.37603 " ±0.0005
Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated V: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified	Shaft Diameter:	1.12382 " ±0.0002
Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated P: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Reach Certified Cengineering Preferences: Conducts Electricity Corrosion Resistant	Temperature	
Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Re	Max Temp F / C:	220 / 104
Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Reach Certified Reach Certified Reach Certified	Min Temp F / C:	-10 / -23
Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Reach Certified Engineering Preferences: Conducts Electricity Corrosion Resistant	Pressure Ratings	
Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Engineering Preferences: Conducts Electricity Corrosion Resistant	Max P:	2000 (psi)
Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Engineering Preferences: Conducts Electricity Corrosion Resistant	Max V:	1200 (sf/m)
Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Engineering Preferences: Conducts Electricity Corrosion Resistant	Max PV:	50000 (lb-ft/in ² -min)
Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Engineering Preferences: Conducts Electricity Corrosion Resistant	Calculated P:	0 (psi)
Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Engineering Preferences: Conducts Electricity Corrosion Resistant	Calculated V:	0 (sf/m)
Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Engineering Preferences: Conducts Electricity Corrosion Resistant	Calculated PV:	0 (lb-ft/in ² -min)
Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Engineering Preferences: Conducts Electricity Corrosion Resistant	Material Specifications	
Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified Engineering Preferences: Conducts Electricity Corrosion Resistant	Lubrication:	Self-Lubricating
Corrosion Resistant	Regulations:	Food Contact Certified Lead-Free Conflict Free RoHS Certified
Specifications Met: SAE 841	Engineering Preferences:	
ASTM B-438 GR 1 TYPE 2 CT-1000-K26	Specifications Met:	ASTM B-438 GR 1 TYPE 2

Preferred Supplier -Beemer Precision, Inc. All Products Made in the U.S.A Contact (215) 646-8440 https://oilite.com Beemer Precision, Inc. ("Beemer") supplies these drawings and specifications for illustration purposes only and without representation or warranty of any kind whatsoever. The buyer is solely responsible for determining whether a bearing is suitable for the buyer's application. Dimensions, tolerances, and materials may change at any time. All bearing sales are subject to Beemer's Standard Terms and Conditions of Sale, which may be found <u>here</u> Copyright Beemer Precision, Inc.