

# AA1320-04FC

# Oilite® Food-Contact

## Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR

172.878.

Temp Range -10°F to +220°F



#### **Dimensions & Tolerances**

Nominal ID: 1.125 " ID Max: 1.128 " ID Min: 1.127 "

Nominal OD: 1.375 " OD Max: 1.379 " OD Min: 1.378 " Length: 2.5 " ±0.0075

Weight: 0.289 lbs / 131.1 g

## **Press Fit**

Housing Bore: 1.37603 " ±0.0005 Shaft Diameter: 1.12282 " ±0.0002

#### **Temperature**

Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23

## **Pressure Ratings**

Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in<sup>2</sup>-min)

Calculated P: 0 (psi)

Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in<sup>2</sup>-min)

# **Material Specifications**

Lubrication: Self-Lubricating Regulations: USDA-H1 Certified

**Food Contact Certified** 

Lead-Free Conflict Free **RoHS Certified** Reach Certified

Engineering Preferences: Conducts Electricity

Corrosion Resistant

Specifications Met: SAE 841

**ASTM B-438 GR 1 TYPE 2** 

CT-1000-K26