

# AA1324-01FC

## Oilite® Food-Contact

## Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR

172.878.

Temp Range -10°F to +220°F



#### **Dimensions & Tolerances**

Nominal ID: 1.1875 "

ID Max: 1.189 "

ID Min: 1.188 "

Nominal OD: 1.375 "

OD Max: 1.379 "

OD Min: 1.378 "

Length: 1.5 " ±0.005

Weight: 0.133 lbs / 60.3 g

## **Press Fit**

Housing Bore: 1.37603 " ±0.0005

Shaft Diameter: 1.18379 " ±0.0002

#### **Temperature**

Max Temp F / C: 220 / 104

Min Temp F / C: -10 / -23

## **Pressure Ratings**

Max P: 2000 (psi)

Max V: 1200 (sf/m)

Max PV: 50000 (lb-ft/in<sup>2</sup>-min)

Calculated P: 0 (psi)

Calculated V: 0 (sf/m)

Calculated PV: 0 (lb-ft/in<sup>2</sup>-min)

# **Material Specifications**

Lubrication: Self-Lubricating

Regulations: USDA-H1 Certified

**Food Contact Certified** 

Lead-Free

Conflict Free

RoHS Certified

Reach Certified

Engineering Preferences: Conducts Electricity

Corrosion Resistant

Specifications Met: SAE 841

**ASTM B-438 GR 1 TYPE 2** 

CT-1000-K26