## **Oilite**<sup>®</sup> Synthetic PERFORMANCE DIFFERENCE®

# AA2008-02FC

## **Oilite® Food-Contact**

### Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR 172.878.

Temp Range -10°F to +220°F



#### Dimensions & Tolerances

ID Max: 1.504 " ID Min: 1.503 " Nominal OD: 2 " OD Max: 2.005 " OD Min: 2.0035 " Length: 1.5 " ±0.005 Weight: 0.476 lbs / 215.9 g Press Fit Housing Bore: 2.00135 " ±0.0005 Shaft Diameter: 1.49751 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in <sup>2</sup> -min) Calculated P: 0 (psi) Calculated PV: 0 (lb-ft/in <sup>2</sup> -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified	
Nominal OD: 2 "           OD Max: 2.005 "           OD Min: 2.0035 "           Length: 1.5 " ±0.005           Weight: 0.476 lbs / 215.9 g           Press Fit           Housing Bore: 2.00135 " ±0.0005           Shaft Diameter: 1.49751 " ±0.0002           Temperature           Max Temp F / C: 220 / 104           Min Temp F / C: -10 / -23           Pressure Ratings           Max P: 2000 (psi)           Max V: 1200 (sf/m)           Max PV: 50000 (lb-ft/in <sup>2</sup> -min)           Calculated P: 0 (psi)           Calculated P: 0 (si/m)           Calculated PV: 0 (lb-ft/in <sup>2</sup> -min)           Material Specifications           Lubrication: Self-Lubricating           Regulations: USDA-H1 Certified           Food Contact Certified           Lead-Free	
OD Max: 2.005 "           OD Min: 2.0035 "           Length: 1.5 " ±0.005           Weight: 0.476 lbs / 215.9 g           Press Fit           Housing Bore: 2.00135 " ±0.0005           Shaft Diameter: 1.49751 " ±0.0002           Temperature           Max Temp F / C: 220 / 104           Min Temp F / C: -10 / -23           Pressure Ratings           Max P: 2000 (psi)           Max V: 1200 (sf/m)           Max PV: 50000 (lb-ft/in <sup>2</sup> -min)           Calculated P: 0 (psi)           Calculated PV: 0 (lb-ft/in <sup>2</sup> -min)           Material Specifications           Lubrication: Self-Lubricating           Regulations: USDA-H1 Certified           Food Contact Certified           Lead-Free	
OD Min: 2.0035 "         Length: 1.5 " ±0.005         Weight: 0.476 lbs / 215.9 g         Press Fit         Housing Bore: 2.00135 " ±0.0005         Shaft Diameter: 1.49751 " ±0.0002         Temperature         Max Temp F / C: 220 / 104         Min Temp F / C: -10 / -23         Pressure Ratings         Max P: 2000 (psi)         Max V: 1200 (sf/m)         Max PV: 50000 (lb-ft/in <sup>2</sup> -min)         Calculated P: 0 (psi)         Calculated V: 0 (sf/m)         Calculated PV: 0 (lb-ft/in <sup>2</sup> -min)         Material Specifications         Lubrication: Self-Lubricating         Regulations: USDA-H1 Certified         Food Contact Certified         Food Contact Certified	
Length: 1.5 " ±0.005 Weight: 0.476 lbs / 215.9 g Press Fit Housing Bore: 2.00135 " ±0.0005 Shaft Diameter: 1.49751 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max V: 1200 (sf/m) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated PV: 0 (lb-ft/in <sup>2</sup> -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Weight: 0.476 lbs / 215.9 g         Press Fit         Housing Bore: 2.00135 " ±0.0005         Shaft Diameter: 1.49751 " ±0.0002         Temperature         Max Temp F / C: 220 / 104         Min Temp F / C: 220 / 104         Min Temp F / C: -10 / -23         Pressure Ratings         Max P: 2000 (psi)         Max V: 1200 (sf/m)         Max PV: 50000 (lb-ft/in <sup>2</sup> -min)         Calculated P: 0 (psi)         Calculated V: 0 (sf/m)         Calculated PV: 0 (lb-ft/in <sup>2</sup> -min)         Material Specifications         Lubrication: Self-Lubricating         Regulations: USDA-H1 Certified         Food Contact Certified         Food Contact Certified	
Press Fit Housing Bore: 2.00135 " ±0.0005 Shaft Diameter: 1.49751 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in <sup>2</sup> -min) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in <sup>2</sup> -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Housing Bore: 2.00135 " ±0.0005 Shaft Diameter: 1.49751 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in <sup>2</sup> -min) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in <sup>2</sup> -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Shaft Diameter: 1.49751 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max V: 1200 (sf/m) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in <sup>2</sup> -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Temperature         Max Temp F / C: 220 / 104         Min Temp F / C: -10 / -23         Pressure Ratings         Max P: 2000 (psi)         Max V: 1200 (sf/m)         Max PV: 50000 (lb-ft/in <sup>2</sup> -min)         Calculated P: 0 (psi)         Calculated V: 0 (sf/m)         Calculated PV: 0 (lb-ft/in <sup>2</sup> -min)         Material Specifications         Lubrication: Self-Lubricating         Regulations: USDA-H1 Certified         Food Contact Certified         Lead-Free	
Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in <sup>2</sup> -min) Calculated P: 0 (psi) Calculated P: 0 (sf/m) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in <sup>2</sup> -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max V: 1200 (sf/m) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in <sup>2</sup> -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in <sup>2</sup> -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in <sup>2</sup> -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in <sup>2</sup> -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in <sup>2</sup> -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in <sup>2</sup> -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in <sup>2</sup> -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Max PV: 50000 (lb-ft/in <sup>2</sup> -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in <sup>2</sup> -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in <sup>2</sup> -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in <sup>2</sup> -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Calculated PV: 0 (lb-ft/in <sup>2</sup> -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Regulations: USDA-H1 Certified Food Contact Certified Lead-Free	
Food Contact Certified Lead-Free	
Conflict Free RoHS Certified Reach Certified	
Engineering Preferences: Conducts Electricity Corrosion Resistant	
Specifications Met: SAE 841 ASTM B-438 GR 1 TYPE 2 CT-1000-K26	

Beemer Precision, Inc. ("Beemer") supplies these drawings and specifications for illustration purposes only and without representation or warranty of any kind whatsoever. The buyer is solely responsible for determining whether a bearing is suitable for the buyer's application. Dimensions, tolerances, and materials may change at any time. All bearing sales are subject to Beemer's Standard Terms and Conditions of Sale, which may be found <u>here</u> Copyright Beemer Precision, Inc.