

# AA226-02FC

# Oilite® Food-Contact

#### Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR

172.878.

Temp Range -10°F to +220°F



#### **Dimensions & Tolerances**

Nominal ID: 0.1875 " ID Max: 0.1885 "

ID Min: 0.1875 "

Nominal OD: 0.25 "

OD Max: 0.252 "

OD Min: 0.251 "

Length: 0.375 " ±0.005

Weight: 0.002 lbs / 0.9 g

#### **Press Fit**

**Temperature** 

Housing Bore: 0.24982 " ±0.0005 Shaft Diameter: 0.1845 " ±0.0002

Onan Blan

Max Temp F / C: 220 / 104

Min Temp F / C: -10 / -23

### **Pressure Ratings**

Max P: 2000 (psi)

Max V: 1200 (sf/m)

Max PV: 50000 (lb-ft/in<sup>2</sup>-min)

Calculated P: 0 (psi)
Calculated V: 0 (sf/m)

Calculated PV: 0 (lb-ft/in<sup>2</sup>-min)

## **Material Specifications**

Lubrication: Self-Lubricating

Regulations: USDA-H1 Certified

Food Contact Certified

Lead-Free
Conflict Free

RoHS Certified Reach Certified

Engineering Preferences: Conducts Electricity

Corrosion Resistant

Specifications Met: SAE 841

**ASTM B-438 GR 1 TYPE 2** 

CT-1000-K26