

## AA3005-01FC

### Oilite® Food-Contact

#### Sleeve

Sintered Bronze Impregnated with Food  
Grade Mineral Oil: FDA 21 CFR  
172.878.

Temp Range -10°F to +220°F



#### Dimensions & Tolerances

Nominal ID: 2.5 "  
ID Max: 2.504 "  
ID Min: 2.5025 "  
Nominal OD: 3 "  
OD Max: 3.005 "  
OD Min: 3.003 "  
Length: 3 " ±0.0075  
Weight: 1.506 lbs / 683.1 g

#### Press Fit

Housing Bore: 3.00065 " ±0.0005  
Shaft Diameter: 2.49638 " ±0.0002

#### Temperature

Max Temp F / C: 220 / 104  
Min Temp F / C: -10 / -23

#### Pressure Ratings

Max P: 2000 (psi)  
Max V: 1200 (sf/m)  
Max PV: 50000 (lb-ft/in<sup>2</sup>-min)  
Calculated P: 0 (psi)  
Calculated V: 0 (sf/m)  
Calculated PV: 0 (lb-ft/in<sup>2</sup>-min)

#### Material Specifications

Lubrication: Self-Lubricating  
Regulations: USDA-H1 Certified  
Food Contact Certified  
Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Corrosion Resistant  
Specifications Met: SAE 841  
ASTM B-438 GR 1 TYPE 2  
CT-1000-K26