## **Oilite**<sup>®</sup> SYNTHETIC PERFORMANCE DIFFERENCE®

# AA304-21FC

# **Oilite® Food-Contact**

### Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR 172.878.

Temp Range -10°F to +220°F



#### **Dimensions & Tolerances**

ID Max: 0.2505 " ID Min: 0.2495 " Nominal OD: 0.375 " OD Max: 0.377 " OD Min: 0.376 " Length: 0.875 " ±0.005 Weight: 0.013 lbs / 5.9 g Press Fit Housing Bore: 0.37474 " ±0.0005 Shaft Diameter: 0.24639 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in <sup>2</sup> -min)	
Nominal OD: 0.375 " OD Max: 0.377 " OD Min: 0.376 " Length: 0.875 " ±0.005 Weight: 0.013 lbs / 5.9 g Press Fit Housing Bore: 0.37474 " ±0.0005 Shaft Diameter: 0.24639 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m)	
OD Max: 0.377 " OD Min: 0.376 " Length: 0.875 " ±0.005 Weight: 0.013 lbs / 5.9 g Press Fit Housing Bore: 0.37474 " ±0.0005 Shaft Diameter: 0.24639 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m)	
OD Min: 0.376 " Length: 0.875 " ±0.005 Weight: 0.013 lbs / 5.9 g Press Fit Housing Bore: 0.37474 " ±0.0005 Shaft Diameter: 0.24639 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m)	
Length: 0.875 " ±0.005 Weight: 0.013 lbs / 5.9 g Press Fit Housing Bore: 0.37474 " ±0.0005 Shaft Diameter: 0.24639 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m)	
Weight: 0.013 lbs / 5.9 g           Press Fit           Housing Bore: 0.37474 " ±0.0005           Shaft Diameter: 0.24639 " ±0.0002           Temperature           Max Temp F / C: 220 / 104           Min Temp F / C: -10 / -23           Pressure Ratings           Max P: 2000 (psi)           Max V: 1200 (sf/m)	
Press Fit Housing Bore: 0.37474 " ±0.0005 Shaft Diameter: 0.24639 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m)	
Housing Bore: 0.37474 " ±0.0005 Shaft Diameter: 0.24639 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m)	
Shaft Diameter: 0.24639 " ±0.0002           Temperature         Max Temp F / C: 220 / 104           Min Temp F / C: -10 / -23         Pressure Ratings           Max P: 2000 (psi)         Max V: 1200 (sf/m)	
Temperature           Max Temp F / C: 220 / 104           Min Temp F / C: -10 / -23           Pressure Ratings           Max P: 2000 (psi)           Max V: 1200 (sf/m)	
Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m)	
Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m)	
Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m)	
Max P: 2000 (psi) Max V: 1200 (sf/m)	
Max V: 1200 (sf/m)	
Max PV: 50000 (lb-ft/in <sup>2</sup> -min)	
	)
Calculated P: 0 (psi)	
Calculated V: 0 (sf/m)	
Calculated PV: 0 (lb-ft/in <sup>2</sup> -min)	
Material Specifications	
Lubrication: Self-Lubricating	
Regulations: USDA-H1 Certified Food Contact Certif Lead-Free Conflict Free RoHS Certified Reach Certified	ied
Engineering Preferences: Conducts Electricity Corrosion Resistant	
Specifications Met: SAE 841 ASTM B-438 GR 1 CT-1000-K26	TYPE 2

Preferred Supplier -Beemer Precision, Inc. All Products Made in the U.S.A Contact (215) 646-8440 https://oilite.com Beemer Precision, Inc. ("Beemer") supplies these drawings and specifications for illustration purposes only and without representation or warranty of any kind whatsoever. The buyer is solely responsible for determining whether a bearing is suitable for the buyer's application. Dimensions, tolerances, and materials may change at any time. All bearing sales are subject to Beemer's Standard Terms and Conditions of Sale, which may be found <u>here</u> Copyright Beemer Precision, Inc.