

AA3201-07FC

Oilite® Food-Contact

Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR

172.878.

Temp Range -10°F to +220°F



Dimensions & Tolerances

Nominal ID: 2.75 " ID Max: 2.752 "

ID Min: 2.75 "

Nominal OD: 3.25 "

OD Max: 3.254 "

OD Min: 3.252 "

Length: 3 " ±0.0075

Weight: 1.636 lbs / 742.1 g

Press Fit

Housing Bore: 3.24947 " ±0.0005 Shaft Diameter: 2.7441 " ±0.0002

Temperature

Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23

Pressure Ratings

Max P: 2000 (psi)
Max V: 1200 (sf/m)

Max PV: 50000 (lb-ft/in²-min)

Calculated P: 0 (psi)
Calculated V: 0 (sf/m)

Calculated PV: 0 (lb-ft/in²-min)

Material Specifications

Lubrication: Self-Lubricating

Regulations: USDA-H1 Certified

Food Contact Certified

Lead-Free Conflict Free RoHS Certified Reach Certified

Engineering Preferences: Conducts Electricity

Corrosion Resistant

Specifications Met: SAE 841

ASTM B-438 GR 1 TYPE 2

CT-1000-K26