Oilite[®] Synthetic PERFORMANCE DIFFERENCE®

AA5664-03FC

Oilite® Food-Contact

Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR 172.878.

Temp Range -10°F to +220°F



Dimensions & Tolerances

$ID Max: 3.507 "$ $ID Min: 3.505 "$ Nominal OD: 4 " $OD Max: 4.008 "$ $OD Max: 4.008 "$ $OD Min: 4.0055 "$ $Length: 4 " \pm 0.01$ Weight: 2.728 lbs / 1237.4 g $Press Fit$ Housing Bore: 4.00294 " \pm 0.0005 Shaft Diameter: 3.49825 " ± 0.0002 $Temperature$ $Max Temp F / C: 220 / 104$ $Min Temp F / C: -10 / -23$ $Pressure Ratings$ $Max P: 2000 (psi)$ $Max V: 1200 (sf/m)$ $Max PV: 50000 (lb-ft/in2-min)$ $Calculated P: 0 (psi)$	
Nominal OD: 4 " OD Max: 4.008 " OD Min: 4.0055 " Length: 4 " ±0.01 Weight: 2.728 lbs / 1237.4 g Press Fit Housing Bore: 4.00294 " ±0.0005 Shaft Diameter: 3.49825 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi)	
OD Max: 4.008 " OD Min: 4.0055 " Length: 4 " ±0.01 Weight: 2.728 lbs / 1237.4 g Press Fit Housing Bore: 4.00294 " ±0.0005 Shaft Diameter: 3.49825 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi)	
OD Min: 4.0055 " Length: 4 " ±0.01 Weight: 2.728 lbs / 1237.4 g Press Fit Housing Bore: 4.00294 " ±0.0005 Shaft Diameter: 3.49825 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi)	
Length: 4 " ±0.01 Weight: 2.728 lbs / 1237.4 g Press Fit Housing Bore: 4.00294 " ±0.0005 Shaft Diameter: 3.49825 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi)	
Weight: 2.728 lbs / 1237.4 g Press Fit Housing Bore: 4.00294 " ±0.0005 Shaft Diameter: 3.49825 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: 220 / 104 Max Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi)	
Press Fit Housing Bore: 4.00294 " ±0.0005 Shaft Diameter: 3.49825 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi)	
Housing Bore: 4.00294 " ±0.0005 Shaft Diameter: 3.49825 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (Ib-ft/in ² -min) Calculated P: 0 (psi)	
Shaft Diameter: 3.49825 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi)	
Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi)	
Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi)	
Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi)	
Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi)	
Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi)	
Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi)	
Max PV: 50000 (Ib-ft/in ² -min) Calculated P: 0 (psi)	
Calculated P: 0 (psi)	
Calculated V: 0 (sf/m)	
Calculated PV: 0 (lb-ft/in ² -min)	
Material Specifications	
Lubrication: Self-Lubricating	
Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified Reach Certified	
Engineering Preferences: Conducts Electricity Corrosion Resistant	
Specifications Met: SAE 841 ASTM B-438 GR 1 TYPE 2 CT-1000-K26	

Beemer Precision, Inc. ("Beemer") supplies these drawings and specifications for illustration purposes only and without representation or warranty of any kind whatsoever. The buyer is solely responsible for determining whether a bearing is suitable for the buyer's application. Dimensions, tolerances, and materials may change at any time. All bearing sales are subject to Beemer's Standard Terms and Conditions of Sale, which may be found <u>here</u> Copyright Beemer Precision, Inc.