Oilite[®] SYNTHETIC PERFORMANCE DIFFERENCE®

AA620-07FC

Oilite® Food-Contact

Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR 172.878.

Temp Range -10°F to +220°F



Dimensions & Tolerances

ID Max: 0.5635 " ID Min: 0.5625 " Nominal OD: 0.6875 " OD Max: 0.691 " OD Min: 0.69 " Length: 0.5 " ±0.005 Weight: 0.015 lbs / 6.8 g Press Fit Housing Bore: 0.68852 " ±0.0005 Shaft Diameter: 0.55903 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: 220 / 104 Min Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (b-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RodHS Certified Read-Free Conflict Free RodHS Certified Read-Certified	Nominal ID:	0.5625 "
Nominal OD: 0.6875 " OD Max: 0.691 " OD Min: 0.69 " Length: 0.5 " ±0.005 Weight: 0.015 lbs / 6.8 g Press Fit Housing Bore: 0.68852 " ±0.0005 Shaft Diameter: 0.55903 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max V: 1200 (sf/m) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated V: 0 (sf/m) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	ID Max:	0.5635 "
OD Max: 0.691 " OD Min: 0.69 " Length: 0.5 " ±0.005 Weight: 0.015 lbs / 6.8 g Press Fit Housing Bore: 0.68852 " ±0.0005 Shaft Diameter: 0.55903 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max V: 1200 (sf/m) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated V: 0 (sf/m) Calculated V: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	ID Min:	0.5625 "
OD Min: 0.69 " Length: 0.5 " ±0.005 Weight: 0.015 lbs / 6.8 g Press Fit Housing Bore: 0.68852 " ±0.0005 Shaft Diameter: 0.55903 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max V: 1200 (sf/m) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated P: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Nominal OD:	0.6875 "
Length: 0.5 " ±0.005 Weight: 0.015 lbs / 6.8 g Press Fit Housing Bore: 0.68852 " ±0.0005 Shaft Diameter: 0.55903 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max V: 1200 (sf/m) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated P: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	OD Max:	0.691 "
Weight: 0.015 lbs / 6.8 g Press Fit Housing Bore: 0.68852 " ±0.0005 Shaft Diameter: 0.55903 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: 220 / 104 Max Temp F / C: 220 / 104 Min Temp F / C: 220 / 104 Min Temp F / C: 200 / 104 Max Temp F / C: 200 / 104 Min Temp F / C: 200 / 104 Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Free Conflict Free RoHS Certified	OD Min:	0.69 "
Press Fit Housing Bore: 0.68852 " ±0.0005 Shaft Diameter: 0.55903 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max V: 1200 (sf/m) Calculated P: 0 (psi) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Length:	0.5 " ±0.005
Housing Bore: 0.68852 " ±0.0005 Shaft Diameter: 0.55903 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated P: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Weight:	0.015 lbs / 6.8 g
Shaft Diameter: 0.55903 " ±0.0002 Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated P: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Press Fit	
Temperature Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Housing Bore:	0.68852 " ±0.0005
Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated P: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Shaft Diameter:	0.55903 " ±0.0002
Min Temp F / C: -10 / -23 Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max V: 1200 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Temperature	
Pressure Ratings Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Max Temp F / C:	220 / 104
Max P: 2000 (psi) Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Min Temp F / C:	-10 / -23
Max V: 1200 (sf/m) Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Pressure Ratings	
Max PV: 50000 (lb-ft/in ² -min) Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Max P:	2000 (psi)
Calculated P: 0 (psi) Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Max V:	1200 (sf/m)
Calculated V: 0 (sf/m) Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Max PV:	50000 (lb-ft/in ² -min)
Calculated PV: 0 (lb-ft/in ² -min) Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Calculated P:	0 (psi)
Material Specifications Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Calculated V:	0 (sf/m)
Lubrication: Self-Lubricating Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Calculated PV:	0 (lb-ft/in ² -min)
Regulations: USDA-H1 Certified Food Contact Certified Lead-Free Conflict Free RoHS Certified	Material Specifications	
Food Contact Certified Lead-Free Conflict Free RoHS Certified	Lubrication:	Self-Lubricating
	Regulations:	Food Contact Certified Lead-Free Conflict Free RoHS Certified
Engineering Preferences: Conducts Electricity Corrosion Resistant	Engineering Preferences:	
Specifications Met: SAE 841 ASTM B-438 GR 1 TYPE 2 CT-1000-K26	Specifications Met:	ASTM B-438 GR 1 TYPE 2

Preferred Supplier -Beemer Precision, Inc. All Products Made in the U.S.A Contact (215) 646-8440 https://oilite.com Beemer Precision, Inc. ("Beemer") supplies these drawings and specifications for illustration purposes only and without representation or warranty of any kind whatsoever. The buyer is solely responsible for determining whether a bearing is suitable for the buyer's application. Dimensions, tolerances, and materials may change at any time. All bearing sales are subject to Beemer's Standard Terms and Conditions of Sale, which may be found <u>here</u> Copyright Beemer Precision, Inc.