## **Oilite**<sup>®</sup> SYNTHETIC PERFORMANCE DIFFERENCE®

# AA811-03FC

## **Oilite® Food-Contact**

### Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR 172.878.

Temp Range -10°F to +220°F



#### Dimensions & Tolerances

	1200 (sf/m)
Calculated P:	0 (psi)
Calculated V:	0 (sf/m)
	0 (lb-ft/in <sup>2</sup> -min)
	0 (lb-ft/in <sup>2</sup> -min)
Material Specifications	
-	Colf Lubricotion
Lubrication:	Self-Lubricating
Regulations:	USDA-H1 Certified
Regulations.	
	Conflict Free
	RoHS Certified
Engineering Preferences:	Conducts Electricity
<b>-</b>	
Specifications Met:	SAE 841
•	ASTM B-438 GR 1 TYPE 2
	CT-1000-K26
	ASTM B-438 GR 1 TYPE 2
	ASTM B-438 GR 1 TYPE 2
	ASTM B-438 GR 1 TYPE 2
	ASTM B-438 GR 1 TYPE 2
	ASTM B-438 GR 1 TYPE 2
	ASTM B-438 GR 1 TYPE 2
Specifications Met.	
Specifications Met:	SAE 841
Specifications Met	SAE 841
Specifications Met	SAF 841
Specifications Met	SAE 8/1
Specifications Mat	SAE 9/1
	Corrosion Resistant
	Corrosion Resistant
Engineering Preferences:	
Engineering Preferences	Conducts Electricity
	Reach Certilled
	Reach Certified
	Conflict Free
	Lead-Free
	Food Contact Certified
regulations.	
Regulations:	USDA-H1 Certified
Poquilationa	USDA-H1 Certified
Lubrication:	Self-Lubricating
-	Self-Lubricating
-	
Calculated P:	0 (psi)
Max PV:	50000 (lb-ft/in <sup>2</sup> -min)
Max P:	2000 (psi)
Pressure Ratings	
Min Temp F / C:	-10/-23
Max Temp F / C:	220 / 104
Temperature	
Shaft Diameter:	0.62242 " ±0.0002
	0.81243 " ±0.0005
Press Fit	0.04040
	0.074 lbs / 33.6 g
	1.5 " ±0.005
OD Min:	0.814 "
OD Max:	0.815 "
Nominal OD:	0.8125 "
ID Min:	0.626 "
ID Max:	0.627 "
Nominal ID:	0.625

Preferred Supplier -Beemer Precision, Inc. All Products Made in the U.S.A Contact (215) 646-8440 https://oilite.com Beemer Precision, Inc. ("Beemer") supplies these drawings and specifications for illustration purposes only and without representation or warranty of any kind whatsoever. The buyer is solely responsible for determining whether a bearing is suitable for the buyer's application. Dimensions, tolerances, and materials may change at any time. All bearing sales are subject to Beemer's Standard Terms and Conditions of Sale, which may be found <u>here</u> Copyright Beemer Precision, Inc.