



## AA921-04

**Oilite**<sup>®</sup>

**Sleeve**

Sintered Bronze Impregnated with Synthetic Performance

Difference™ AM1-SPD™

Temp Range -35°F to +300°F

### Dimensions & Tolerances

Nominal ID: 0.75 "   
 ID Max: 0.7515 "   
 ID Min: 0.7505 "   
 Nominal OD: 0.9375 "   
 OD Max: 0.94 "   
 OD Min: 0.939 "   
 Length: 1 " ±0.005   
 Weight: 0.059 lbs / 26.8 g

### Press Fit

Housing Bore: 0.93734 " ±0.0005   
 Shaft Diameter: 0.74678 " ±0.0002

### Temperature

Max Temp F / C: 300 / 149   
 Min Temp F / C: -35 / -37

### Pressure Ratings

Max P: 2000 (psi)   
 Max V: 1200 (sf/m)   
 Max PV: 50000 (lb-ft/in<sup>2</sup>-min)   
 Calculated P: 0 (psi)   
 Calculated V: 0 (sf/m)   
 Calculated PV: 0 (lb-ft/in<sup>2</sup>-min)

### Material Specifications

Lubrication: Self-Lubricating   
 Regulations: Lead-Free   
 Conflict Free   
 RoHS Certified   
 Reach Certified   
 Engineering Preferences: Conducts Electricity   
 Corrosion Resistant   
 Specifications Met: SAE 841   
 ASTM B-438 GR 1 TYPE 2   
 CT-1000-K26