

## AAM0408-08FC

# Oilite® M-Series Food-Contact

### Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR

172.878.

Temp Range -23°C to +100°C



### **Dimensions & Tolerances**

Nominal ID: 4 mm
ID Max: 4.02 mm
ID Min: 4 mm
Nominal OD: 8 mm

OD Max: 8.04 mm
OD Min: 8.02 mm
Length: 8 mm ±0.127

Weight: 0.005 lbs / 2.3 g

## **Press Fit**

Housing Bore:  $7.98357 \text{ mm} \pm 0.013$ Shaft Diameter:  $3.91772 \text{ mm} \pm 0.005$ 

### **Temperature**

Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23

## **Pressure Ratings**

Max P: 13.78 (N/mm<sup>2</sup>) Max V: 6.1 (m/s)

Max PV: 1.75 (N-M/mm<sup>2</sup>-s)
Calculated P: 0 (N/mm<sup>2</sup>)
Calculated V: 0 (m/s)

Calculated PV: 0 (N-M/mm<sup>2</sup>-s)

## **Material Specifications**

Lubrication: Self-Lubricating
Regulations: USDA-H1 Certified

**Food Contact Certified** 

Lead-Free Conflict Free RoHS Certified Reach Certified

Engineering Preferences: Conducts Electricity

Corrosion Resistant

Specifications Met: SAE 841

**ASTM B-438 GR 1 TYPE 2** 

CT-1000-K26