



AAM0609-16NT

Oilite[®] M-Series Metric Non-Tox

Sleeve

USDA H1 Approved Synthetic Lubricant:
Non-Tox-SPD™. For Incidental Food
Contact Applications Temp Range -59°C
to +175°C

Dimensions & Tolerances

Nominal ID: 6 mm
ID Max: 6.02 mm
ID Min: 6 mm
Nominal OD: 9 mm
OD Max: 9.04 mm
OD Min: 9.02 mm
Length: 16 mm ±0.127
Weight: 0.009 lbs / 4.1 g

Press Fit

Housing Bore: 8.98287 mm ±0.013
Shaft Diameter: 5.91609 mm ±0.005

Temperature

Max Temp F / C: 420 / 216
Min Temp F / C: -75 / -59

Pressure Ratings

Max P: 13.78 (N/mm²)
Max V: 6.1 (m/s)
Max PV: 1.75 (N-M/mm²-s)
Calculated P: 0 (N/mm²)
Calculated V: 0 (m/s)
Calculated PV: 0 (N-M/mm²-s)

Material Specifications

Lubrication: Self-Lubricating
Regulations: USDA-H1 Certified
Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Conducts Electricity
Corrosion Resistant
Specifications Met: SAE 841
ASTM B-438 GR 1 TYPE 2
CT-1000-K26