

## **AAM0811-12FC**

# Oilite® M-Series Food-Contact

### Sleeve

Sintered Bronze Impregnated with Food Grade Mineral Oil: FDA 21 CFR

172.878.

Temp Range -23°C to +100°C



### **Dimensions & Tolerances**

Nominal ID: 8 mm

ID Max: 8.03 mm

ID Min: 8.01 mm Nominal OD: 11 mm

> OD Max: 11.05 mm OD Min: 11.03 mm

Length: 12 mm ±0.127 Weight: 0.011 lbs / 5 g

## **Press Fit**

Housing Bore:  $10.99147 \text{ mm} \pm 0.013$ Shaft Diameter:  $7.92382 \text{ mm} \pm 0.005$ 

### **Temperature**

Max Temp F / C: 220 / 104 Min Temp F / C: -10 / -23

## **Pressure Ratings**

Max P: 13.78 (N/mm<sup>2</sup>)

Max V: 6.1 (m/s)

Max PV: 1.75 (N-M/mm<sup>2</sup>-s)

Calculated P: 0 (N/mm<sup>2</sup>)
Calculated V: 0 (m/s)

Calculated PV: 0 (N-M/mm<sup>2</sup>-s)

## **Material Specifications**

Lubrication: Self-Lubricating

Regulations: USDA-H1 Certified

**Food Contact Certified** 

Lead-Free Conflict Free RoHS Certified Reach Certified

Engineering Preferences: Conducts Electricity

Corrosion Resistant

Specifications Met: SAE 841

**ASTM B-438 GR 1 TYPE 2** 

CT-1000-K26