Oilite[®] SYNTHETIC PERFORMANCE DIFFERENCE®

AAM1014-08

Oilite® M-Series Metric

Sleeve

Sintered Bronze Impregnated with Synthetic Performance Difference™ AM1-SPD™.

Largest Selection of Metric Sizes World Wide.

Temp Range -37°C to +149°C



Dimensions & Toler	ances		
	Nominal ID:	10 mm	
	ID Max:	10.03 mm	
	ID Min:	10.01 mm	
	Nominal OD:	14 mm	
	OD Max:	14.05 mm	
	OD Min:	14.03 mm	
	Length:	8 mm ±0.127	
	Weight:	0.009 lbs / 4.1 g	
Press Fit			
	Housing Bore:	13.98937 mm ±0.013	
	Shaft Diameter:	9.92093 mm ±0.005	
Temperature			
	Max Temp F / C:	300 / 149	
	Min Temp F / C:	-35 / -37	
Pressure Ratings			
	Max P:	13.78 (N/mm ²)	
	Max V:	6.1 (m/s)	
	Max PV:	1.75 (N-M/mm ² -s)	
	Calculated P:	0 (N/mm ²)	
	Calculated V:	0 (m/s)	
	Calculated PV:	0 (N-M/mm ² -s)	
Material Specification	ons		
	Lubrication:	Self-Lubricating	
	Regulations:	Lead-Free Conflict Free RoHS Certified Reach Certified	
Er	ngineering Preferences:	Conducts Electricity Corrosion Resistant	
	Specifications Met:	SAE 841 ASTM B-438 GR 1 TYPE 2 CT-1000-K26	

Preferred Supplier -Beemer Precision, Inc. All Products Made in the U.S.A Contact (215) 646-8440 https://oilite.com Beemer Precision, Inc. ("Beemer") supplies these drawings and specifications for illustration purposes only and without representation or warranty of any kind whatsoever. The buyer is solely responsible for determining whether a bearing is suitable for the buyer's application. Dimensions, tolerances, and materials may change at any time. All bearing sales are subject to Beemer's Standard Terms and Conditions of Sale, which may be found <u>here</u> Copyright Beemer Precision, Inc.