oilite® SYNTHETIC PERFORMANCE DIFFERENCE®



AAM1418-14

Oilite® M-Series Metric

Sleeve

Sintered Bronze Impregnated with Synthetic Performance Difference™ AM1-SPD™.

Largest Selection of Metric Sizes World Wide.

Temp Range -37°C to +149°C

Dimensions & Tolerances

Nominal ID:	14 mm
ID Max:	14.03 mm
ID Min:	14.01 mm
Nominal OD:	18 mm
OD Max:	18.05 mm
OD Min:	18.03 mm
Length:	14 mm ±0.127
Weight:	0.02 lbs / 9.1 g

Press Fit

Housing Bore:	17.98657 mm ±0.013
Shaft Diameter:	13.91641 mm ±0.005

Temperature

Max Temp F / C:	300 / 149
Min Temp F / C:	-35 / -37

Pressure Ratings

Max P:	13.78 (N/mm^2)
Max V:	6.1 (m/s)
Max PV:	1.75 ($N\text{-}M/mm^2\text{-}s$)
Calculated P:	0 (N/mm^2)
Calculated V:	0 (m/s)
Calculated PV:	0 ($N\text{-}M/mm^2\text{-}s$)

Material Specifications

Lubrication:	Self-Lubricating
Regulations:	Lead-Free Conflict Free RoHS Certified Reach Certified
Engineering Preferences:	Conducts Electricity Corrosion Resistant
Specifications Met:	**SAE 841** **ASTM B-438 GR 1 TYPE 2** **CT-1000-K26**

Preferred Supplier -
Beemer Precision, Inc.
All Products Made in the U.S.A
Contact (215) 646-8440
https://oilite.com

Beemer Precision, Inc. (“Beemer”) supplies these drawings and specifications for illustration purposes only and without representation or warranty of any kind whatsoever. The buyer is solely responsible for determining whether a bearing is suitable for the buyer’s application. Dimensions, tolerances, and materials may change at any time. All bearing sales are subject to Beemer’s Standard Terms and Conditions of Sale, which may be found here
Copyright Beemer Precision, Inc.