



## AAM3040-50NT

### Oilite<sup>®</sup> M-Series Metric Non-Tox

#### Sleeve

USDA H1 Approved Synthetic Lubricant:  
Non-Tox-SPD™. For Incidental Food  
Contact Applications Temp Range -59°C  
to +175°C

#### Dimensions & Tolerances

Nominal ID: 30 mm  
ID Max: 30.03 mm  
ID Min: 30.01 mm  
Nominal OD: 40 mm  
OD Max: 40.07 mm  
OD Min: 40.04 mm  
Length: 50 mm  $\pm 0.1905$   
Weight: 0.391 lbs / 177.4 g

#### Press Fit

Housing Bore: 39.9848 mm  $\pm 0.013$   
Shaft Diameter: 29.87614 mm  $\pm 0.005$

#### Temperature

Max Temp F / C: 420 / 216  
Min Temp F / C: -75 / -59

#### Pressure Ratings

Max P: 13.78 (N/mm<sup>2</sup>)  
Max V: 6.1 (m/s)  
Max PV: 1.75 (N-M/mm<sup>2</sup>-s)  
Calculated P: 0 (N/mm<sup>2</sup>)  
Calculated V: 0 (m/s)  
Calculated PV: 0 (N-M/mm<sup>2</sup>-s)

#### Material Specifications

Lubrication: Self-Lubricating  
Regulations: USDA-H1 Certified  
Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Corrosion Resistant  
Specifications Met: SAE 841  
ASTM B-438 GR 1 TYPE 2  
CT-1000-K26