

# AP1212-14

## Oilite®/PLUS

### Sleeve

PTFE Additive-Reduced Friction  
Synthetic Oilite®/Plus-SPD™.

Extreme Performance-Unique  
Applications.

Temp Range -60°F to +300°F



### Dimensions & Tolerances

Nominal ID: 1 "  
ID Max: 1.001 "  
ID Min: 1 "  
Nominal OD: 1.25 "  
OD Max: 1.252 "  
OD Min: 1.251 "  
Length: 3 " ±0.0075  
Weight: 0.307 lbs / 139.3 g

### Press Fit

Housing Bore: 1.24912 " ±0.0005  
Shaft Diameter: 0.99596 " ±0.0002

### Temperature

Max Temp F / C: 300 / 149  
Min Temp F / C: -60 / -51

### Pressure Ratings

Max P: 2000 (psi)  
Max V: 1200 (sf/m)  
Max PV: 50000 (lb-ft/in<sup>2</sup>-min)  
Calculated P: 0 (psi)  
Calculated V: 0 (sf/m)  
Calculated PV: 0 (lb-ft/in<sup>2</sup>-min)

### Material Specifications

Lubrication: Self-Lubricating  
Regulations: Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Corrosion Resistant  
Specifications Met: SAE 841  
ASTM B-438 GR 1 TYPE 2  
CT-1000-K26