



## FF2501-FC

### Oilite<sup>®</sup> Food-Contact

#### Flange

Sintered Bronze Impregnated with Food  
Grade Mineral Oil: FDA 21 CFR  
172.878.

Temp Range -10°F to +220°F

#### Dimensions & Tolerances

Nominal ID: 2 "  
ID Max: 2.002 "  
ID Min: 2.0005 "  
Nominal OD: 2.5 "  
OD Max: 2.501 "  
OD Min: 2.4995 "  
Length: 2.375 " ±0.0075  
Flange OD: 3 " ±0.015  
Flange Thickness: 0.375 " ±0.0025  
Weight: 1.169 lbs / 530.2 g

#### Press Fit

Housing Bore: 2.497 " ±0.0005  
Shaft Diameter: 1.99495 " ±0.0002

#### Temperature

Max Temp F / C: 220 / 104  
Min Temp F / C: -10 / -23

#### Pressure Ratings

Max P: 2000 (psi)  
Max V: 1200 (sf/m)  
Max PV: 50000 (lb-ft/in<sup>2</sup>-min)  
Calculated P: 0 (psi)  
Calculated V: 0 (sf/m)  
Calculated PV: 0 (lb-ft/in<sup>2</sup>-min)

#### Material Specifications

Lubrication: Self-Lubricating  
Regulations: USDA-H1 Certified  
Food Contact Certified  
Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Corrosion Resistant  
Specifications Met: **SAE 841**  
**ASTM B-438 GR 1 TYPE 2**  
**CT-1000-K26**