



FF718-03FC

Oilite[®] Food-Contact

Flange

Sintered Bronze Impregnated with Food
Grade Mineral Oil: FDA 21 CFR
172.878.

Temp Range -10°F to +220°F

Dimensions & Tolerances

Nominal ID: 0.625 "
ID Max: 0.6275 "
ID Min: 0.6265 "
Nominal OD: 0.75 "
OD Max: 0.7525 "
OD Min: 0.7515 "
Length: 1 " ±0.005
Flange OD: 0.875 " ±0.005
Flange Thickness: 0.0625 " ±0.0025
Weight: 0.034 lbs / 15.4 g

Press Fit

Housing Bore: 0.74997 " ±0.0005
Shaft Diameter: 0.62296 " ±0.0002

Temperature

Max Temp F / C: 220 / 104
Min Temp F / C: -10 / -23

Pressure Ratings

Max P: 2000 (psi)
Max V: 1200 (sf/m)
Max PV: 50000 (lb-ft/in²-min)
Calculated P: 0 (psi)
Calculated V: 0 (sf/m)
Calculated PV: 0 (lb-ft/in²-min)

Material Specifications

Lubrication: Self-Lubricating
Regulations: USDA-H1 Certified
Food Contact Certified
Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Conducts Electricity
Corrosion Resistant
Specifications Met: SAE 841
ASTM B-438 GR 1 TYPE 2
CT-1000-K26