



## FFM1622-20B

### Oilite<sup>®</sup> M-Series Metric

#### Flange

Sintered Bronze Impregnated with  
Synthetic Performance  
Difference<sup>™</sup> AM1-SPD<sup>™</sup>.

Largest Selection of Metric Sizes World  
Wide.

Temp Range -37°C to +149°C

#### Dimensions & Tolerances

Nominal ID: 16 mm  
ID Max: 16.03 mm  
ID Min: 16.01 mm  
Nominal OD: 22 mm  
OD Max: 22.06 mm  
OD Min: 22.04 mm  
Length: 20 mm  $\pm 0.127$   
Flange OD: 28 mm  $\pm 0.127$   
Flange Thickness: 3 mm  $\pm 0.0635$   
Weight: 0.55 lbs / 249.5 g

#### Press Fit

Housing Bore: 21.99376 mm  $\pm 0.013$   
Shaft Diameter: 15.91289 mm  $\pm 0.005$

#### Temperature

Max Temp F / C: 300 / 149  
Min Temp F / C: -35 / -37

#### Pressure Ratings

Max P: 13.78 (N/mm<sup>2</sup>)  
Max V: 6.1 (m/s)  
Max PV: 1.75 (N-M/mm<sup>2</sup>-s)  
Calculated P: 0 (N/mm<sup>2</sup>)  
Calculated V: 0 (m/s)  
Calculated PV: 0 (N-M/mm<sup>2</sup>-s)

#### Material Specifications

Lubrication: Self-Lubricating  
Regulations: Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Corrosion Resistant  
Specifications Met: SAE 841  
ASTM B-438 GR 1 TYPE 2  
CT-1000-K26