

FFMP2229-22B

Oilite[®]/PLUS

Flange

PTFE Additive-Reduced Friction
Synthetic Oilite[®]/Plus-SPD[™].

Extreme Performance-Unique
Applications.

Temp Range -60°F to +300°F



Dimensions & Tolerances

Nominal ID: 22 mm
ID Max: 22.03 mm
ID Min: 22.01 mm
Nominal OD: 29 mm
OD Max: 29.06 mm
OD Min: 29.04 mm
Length: 22 mm ± 0.127
Flange OD: 36 mm ± 0.254
Flange Thickness: 3.5 mm ± 0.127
Weight: lbs / 0 g

Press Fit

Housing Bore: 28.98886 mm ± 0.013
Shaft Diameter: 21.90548 mm ± 0.005

Temperature

Max Temp F / C: 300 / 149
Min Temp F / C: -60 / -51

Pressure Ratings

Max P: 2000 (N/mm²)
Max V: 1200 (m/s)
Max PV: 50000 (N-M/mm²-s)
Calculated P: 0 (N/mm²)
Calculated V: 0 (m/s)
Calculated PV: 0 (N-M/mm²-s)

Material Specifications

Lubrication: Self-Lubricating
Regulations: Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Conducts Electricity
Corrosion Resistant
Specifications Met: SAE 841
ASTM B-438 GR 1 TYPE 2
CT-1000-K26