



## FFMP2532-25

### Oilite<sup>®</sup> M-Series Metric/PLUS

#### Flange

PTFE Additive-Reduced Friction  
Synthetic Oilite<sup>®</sup>/Plus-SPD<sup>™</sup>. Extreme  
Performance-Unique Applications.

Temp Range -50°C to +149°C

#### Dimensions & Tolerances

Nominal ID: 25 mm  
ID Max: 25.03 mm  
ID Min: 25.01 mm  
Nominal OD: 32 mm  
OD Max: 32.06 mm  
OD Min: 32.04 mm  
Length: 25 mm  $\pm 0.127$   
Flange OD: 39 mm  $\pm 0.254$   
Flange Thickness: 3.5 mm  $\pm 0.127$   
Weight: 0.13 lbs / 59 g

#### Press Fit

Housing Bore: 31.98676 mm  $\pm 0.013$   
Shaft Diameter: 24.90209 mm  $\pm 0.005$

#### Temperature

Max Temp F / C: 300 / 149  
Min Temp F / C: -60 / -51

#### Pressure Ratings

Max P: 13.78 (N/mm<sup>2</sup>)  
Max V: 6.1 (m/s)  
Max PV: 1.75 (N-M/mm<sup>2</sup>-s)  
Calculated P: 0 (N/mm<sup>2</sup>)  
Calculated V: 0 (m/s)  
Calculated PV: 0 (N-M/mm<sup>2</sup>-s)

#### Material Specifications

Lubrication: Self-Lubricating  
Regulations: Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Corrosion Resistant  
Specifications Met: SAE 841  
ASTM B-438 GR 1 TYPE 2  
CT-1000-K26