Oilite[®] Synthetic PERFORMANCE DIFFERENCE®

PS-0406-02B

Oilite® Polymer Peek

Sleeve

Bearing Grade Material, Chemical Resistance, High Performance, Low Friction, Max PV 25,000



Dimensions & Tolerances

Nominal ID:	0.25 "
ID Max:	0.2535 "
ID Min:	0.2525 "
Nominal OD:	0.375 "
OD Max:	0.3768 "
OD Min:	0.3758 "
Length:	0.25 " ±0.005
Weight:	lbs / 0 g
Press Fit	
Housing Bore:	0.3743 " ±0.0005
Shaft Diameter:	0.24857 " ±0.0002
Temperature	
Max Temp F / C:	500 / 260
Min Temp F / C:	-40 / -40
Pressure Ratings	
Max P:	4500 (psi)
Max V:	500 (sf/m)
Max PV:	25000 (lb-ft/in ² -min)
Calculated P:	0 (psi)
Calculated V:	0 (sf/m)
Calculated PV:	0 (lb-ft/in ² -min)
Material Specifications	
	Self-Lubricating Dry Running
	Lead-Free Conflict Free RoHS Certified Reach Certified
	Washdown Chemical Resistant Corrosion Resistant Electrical Insulation STEAM
Specifications Met:	

Beemer Precision, Inc. ("Beemer") supplies these drawings and specifications for illustration purposes only and without representation or warranty of any kind whatsoever. The buyer is solely responsible for determining whether a bearing is suitable for the buyer's application. Dimensions, tolerances, and materials may change at any time. All bearing sales are subject to Beemer's Standard Terms and Conditions of Sale, which may be found <u>here</u> Copyright Beemer Precision, Inc.