



## SOA1524-13

### Super Oilite<sup>®</sup>

#### Sleeve

Iron-Based Sintered Product  
Impregnated with Extreme Pressure  
Synthetic AM3-SPD™. Higher Load-  
Slower Speed Designs Economic  
Alternative Material.

Temp Range -15°F to +300°F

#### Dimensions & Tolerances

Nominal ID: 1.25 "  
ID Max: 1.254 "  
ID Min: 1.2525 "  
Nominal OD: 1.5 "  
OD Max: 1.504 "  
OD Min: 1.5025 "  
Length: 2 " ±0.015  
Weight: 0.322 lbs / 146.1 g

#### Press Fit

Housing Bore: 1.50035 " ±0.0005  
Shaft Diameter: 1.24734 " ±0.0002

#### Temperature

Max Temp F / C: 300 / 149  
Min Temp F / C: -15 / -26

#### Pressure Ratings

Max P: 4000 (psi)  
Max V: 225 (sf/m)  
Max PV: 35000 (lb-ft/in<sup>2</sup>-min)  
Calculated P: 0 (psi)  
Calculated V: 0 (sf/m)  
Calculated PV: 0 (lb-ft/in<sup>2</sup>-min)

#### Material Specifications

Lubrication: Self-Lubricating  
Regulations: Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Specifications Met: SAE 863  
ASTM B-439 GR 4  
FC-2000-K30