



SOF504-01NT

Super Oilite[®] Non-Tox

Flange

USDA H1 Approved Synthetic Lubricant:
Non-Tox-SPD™. Economic High-Load
Material.

Temp Range -75°F to +350°F

Dimensions & Tolerances

Nominal ID: 0.4375 "
ID Max: 0.439 "
ID Min: 0.438 "
Nominal OD: 0.5625 "
OD Max: 0.565 "
OD Min: 0.564 "
Length: 0.75 " ±0.01
Flange OD: 0.6875 " ±0.01
Flange Thickness: 0.0625 " ±0.005
Weight: 0.02 lbs / 9.1 g

Press Fit

Housing Bore: 0.56235 " ±0.0005
Shaft Diameter: 0.43415 " ±0.0002

Temperature

Max Temp F / C: 350 / 177
Min Temp F / C: -75 / -59

Pressure Ratings

Max P: 4000 (psi)
Max V: 225 (sf/m)
Max PV: 35000 (lb-ft/in²-min)
Calculated P: 0 (psi)
Calculated V: 0 (sf/m)
Calculated PV: 0 (lb-ft/in²-min)

Material Specifications

Lubrication: Self-Lubricating
Regulations: USDA-H1 Certified
Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Conducts Electricity
Specifications Met: SAE 863
ASTM B-439 GR 4
FC-2000-K30