



## SOFM2024-12

### Super Oilite<sup>®</sup> M-Series

#### Metric

#### Flange

Iron-Based Sintered Product  
Impregnated with Extreme Pressure  
Synthetic AM3-SPD™. Higher Load,  
Slower Speed Designs Economic  
Alternative Material.

Temp Range -26°C to +149°C

#### Dimensions & Tolerances

Nominal ID: 20 mm  
ID Max: 20.035 mm  
ID Min: 20.01 mm  
Nominal OD: 24 mm  
OD Max: 24.065 mm  
OD Min: 24.04 mm  
Length: 12 mm ±0.25  
Flange OD: 28 mm ±0.25  
Flange Thickness: 2 mm ±0.125  
Weight: 0.025 lbs / 11.3 g

#### Press Fit

Housing Bore: 23.98987 mm ±0.013  
Shaft Diameter: 19.90027 mm ±0.005

#### Temperature

Max Temp F / C: 300 / 149  
Min Temp F / C: -15 / -26

#### Pressure Ratings

Max P: 27.56 (N/mm<sup>2</sup>)  
Max V: 1.14 (m/s)  
Max PV: 1.225 (N-M/mm<sup>2</sup>-s)  
Calculated P: 0 (N/mm<sup>2</sup>)  
Calculated V: 0 (m/s)  
Calculated PV: 0 (N-M/mm<sup>2</sup>-s)

#### Material Specifications

Lubrication: Self-Lubricating  
Regulations: Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Specifications Met: SAE 863  
ASTM B-439 GR 4  
FC-2000-K30