



SOT2006-NT

Super Oilite[®] Non-Tox

Thrust

USDA H1 Approved Synthetic Lubricant:
Non-Tox-SPD™. Economic High-Load
Material.

Temp Range -75°F to +350°F

Dimensions & Tolerances

Nominal ID: 1.25 "
ID Max: 1.27 "
ID Min: 1.26 "
Nominal OD: 2 "
OD Max: 2.015 "
OD Min: 1.985 "
Length: 0.0625 " ±0.005
Weight: 0.028 lbs / 12.7 g

Press Fit

Housing Bore: 2.01094 " ±0.0005
Shaft Diameter: 1.26296 " ±0.0002

Temperature

Max Temp F / C: 350 / 177
Min Temp F / C: -75 / -59

Pressure Ratings

Max P: 4000 (psi)
Max V: 225 (sf/m)
Max PV: 35000 (lb-ft/in²-min)
Calculated P: 0 (psi)
Calculated V: 0 (sf/m)
Calculated PV: 0 (lb-ft/in²-min)

Material Specifications

Lubrication: Self-Lubricating
Regulations: USDA-H1 Certified
Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Conducts Electricity
Specifications Met: SAE 863
ASTM B-439 GR 4
FC-2000-K30