



TT3800-

Oilite[®]

Thrust

Sintered Bronze Impregnated with
Synthetic Performance

Difference[™] AM1-SPD[™]

Temp Range -35°F to +300°F

Dimensions & Tolerances

Nominal ID: 2.75 "
ID Max: 2.781 "
ID Min: 2.616 "
Nominal OD: 3.875 "
OD Max: 3.895 "
OD Min: 3.855 "
Length: 0.25 " ±0.0025
Weight: 0.344 lbs / 156 g

Press Fit

Housing Bore: 3.89002 " ±0.0005
Shaft Diameter: 2.77268 " ±0.0002

Temperature

Max Temp F / C: 300 / 149
Min Temp F / C: -35 / -37

Pressure Ratings

Max P: 2000 (psi)
Max V: 1200 (sf/m)
Max PV: 50000 (lb-ft/in²-min)
Calculated P: 0 (psi)
Calculated V: 0 (sf/m)
Calculated PV: 0 (lb-ft/in²-min)

Material Specifications

Lubrication: Self-Lubricating
Regulations: Lead-Free
Conflict Free
RoHS Certified
Reach Certified
Engineering Preferences: Conducts Electricity
Corrosion Resistant
Specifications Met: SAE 841
ASTM B-438 GR 1 TYPE 2
CT-1000-K26